

OP2720 Series POE Ethernet Switch



OP2720 series Ethernet switches are ZISA developed green energy Gigabit Ethernet switch, with rich service features, widely used in corporate networks and campus network access. On the basis of access to meet the high performance, providing more comprehensive security access policies and greater ease of network management and maintenance, the switch is ideal for access.

Product Features

- High performance and the flexibility to expand capacity
- Rich security policy
- Enhanced multi-service capabilities
- Enhanced Power over Ethernet capability (PoE +)
- Professional lightning protection
- Green energy
- Easy to use network management

Product Specification

Item	OP2720-10T	OP2720-28T
Switching capacity	256Gbps	
Packet forwarding rate	14.88Mpps	41.67Mpps
management port	One Console	
port	8*10/100/1000Base-T Ethernet 2*1000Base-X Ethernet	24*10/100/1000Base-T Ethernet 4*1000Base-X Ethernet
PoE	Support IEEE 802.3at PoE+	
Aggregation	Support manual Aggregation , 8 ports MAX	
VLAN	Support VLAN based port (512) Support VLAN Mapping Support GUEST VLAN	

DHCP	Support DHCP Client	
IGMP	Support IGMP Snooping Support multicast VLAN	
Mirror	Support port mirror	
	Support Diff-Serv QoS Support 8 output queues of every port Support 802.1p/DSCP priority mapping Support Queue scheduling Support Based on the flow of redirection Support based on the limit speed	
safety	The user classification management, and password protection Support Guest VLAN Support MAC learning number limit Support hole MAC Support SSH 2.0 Support port isolate Support ARP speed limit Support IP source address protect Support ARP invasion measure the function Support anti-Dos attack Support broadcast inhibition Support IP + port binding, IP+MAC binding, port + MAC binding, IP+MAC+port binding, IP+MAC+port+VLAN binding Support CPU protection function	
System management	Support WEB/Console/Telnet/SSH2.0 Support FTP、TFTP、Xmodem、SFTP Support NTP Support System log	
environment temperature	running : 0°C ~ 45°C storage : -40°C ~ 70°C	
Environment humidity	running : 5% ~ 95% storage : 5% ~ 95%	
environmental protection	China RoHs,、 EEE	
PoE+	Support PoE+ max power:190W Port maximum power: 30W	Support PoE+ max power:385W Port maximum power:30W
WIGHT	≤ 2.5kg	≤ 4kg
Static Power	13W	20W

full power	≤ 235W , include PoETotal power 190W	≤474W , include PoETotal power 385W
Input Voltage	AC : 100V ~ 240V AC , 50/60Hz	
Dimension (length×with×high)(mm)	330×230×44 (-PWR)	440×260×44 (-PWR)

■ **Connect us**

ZISA Corporation LIMITED

Mail to : sales@zisacom.com.cn

URL: <http://www.zisacom.com.cn>

Specifications are subject to change without notice.

Copyright © ZISA Corp. All rights reserved.